

## Value Based Desktop Printing!

Label printing has never been easier



### Durable Internal Power Supply

The CL-S300 features an internal main power supply which reduces the footprint and avoids cable routing issues. The internal supply also adds weight and stability to the printer unit.



### GDI

By using the Windows™ Graphical Device Interface (GDI) you can print from any application you like using the Windows™ driver.

CITIZEN CL-S300  
LABEL

### Applications

- Parcel-Post/Courier
- SME / SMB
- E-Seller
- Retail
- Healthcare
- Services



### Easy Operation and Media Change

The single button and Citizen's unique Hi-Open™ housing make it easy to operate the printer even for non-skilled users.

[www.citizen-systems.com](http://www.citizen-systems.com)



## USB interface

With a full speed USB 2.0 interface on board the CL-S300 is ready to work out of the box.

## Specifications

Technology	Direct Thermal
Resolution	203 dpi (8 dots per mm)
Print Speed (maximum)	4 inches per second (102 mm/s)
Print Width (maximum)	4.25 inches (108 mm)
Media Width (min to max)	1 inch to 4.64 inches (25.4 mm to 118 mm)
Media Thickness (min to max)	0.003 to 0.008 inches (0.06 to 0.2 mm)
Media Sensor	Fixed label gap and black mark
Media Length (min to max)	1.5 inches to 68 inches (38.1 mm to 1727 mm)
Roll Size (max), Core size	5 inches (127 mm) diameter, 1 / 1.5 inches (25,4 mm / 38,1 mm) core
Interface	USB (version 2.0, full speed)
Case	Hi-Open™
Mechanism	Self-contained
Panel	One LED, Control key: FEED
Flash (Non-Volatile Memory)	64KB Flash, 16KB SDRAM
Windows® drivers and software	Supporting XP®, 2003, 2008, Vista™, 7, 8
Size (W x D x H) and Weight	168 x 222 x 178 mm, 2.0 Kg / 6.61 x 8.74 x 7.00 in, 4.41 lbs
Printer, Head Warranty	2 Years for Printer; 30 Kms/6 months on head

Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

## CITIZEN CL-S300

LABEL

## Features & Benefits

- Hi-Open™ housing for easy media loading
- Self-contained mechanism for durable operation
- Compact design
- Single button control panel
- Built-in power supply, AC100-240V 1.6A(Max) 50/60Hz
- Fixed label sensor
- Standard tear-bar for perforated tags
- Internal USB interface
- Media roll holder





800 729 0236  
www.logiscenter.us



0241 9550 9225  
www.logiscenter.de



01 82 88 44 70  
www.logiscenter.fr



020 3318 8265  
www.logiscenter.co.uk



0720 115814  
www.logiscenter.at



02 58 80 583  
www.logiscenter.be



911 433 048  
www.logiscenter.com



02 4792 1697  
www.logiscenter.it



308 800 842  
www.logiscenter.pt

## About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permanent stock of more than 60,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.

**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.



## All Brands Technical Service


## Our Brands




## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables  
(labels, ribbons, PVC cards)